

Value+

Forehead IR Thermometers

- Large Display shows :
 - T1, T2 together (VT55A); and
 - T1, T2, T3, T4 together (VT55B);
- Electronic offset function allows compensation of thermocouple errors to maximise overall accuracy;
- Measures J, K, T, E, R, S and N type thermocouples;
- Readout in °C, °F or Kelvin (K);
- Data logging up to 5000 records (VT55B) or 100 records (VT55A);
- With Hi / Lo Alarm to keep inform user when Hi or Low temperature is recorded;
- User friendly front panel is easy to set up and operate
- Auto Power Off to increase battery life.



Contact Type Thermometers



		VT55A	VT55B
No of Input		2	4
Temperature	Type K	-200°C ~ 1300°C ±(2%+2°C) -328°F ~ 2372°F ±(2%+4°F)	±(1%+1°C) ±(1%+2°F)
	Type J	-200°C ~ 1200°C ±(2%+2°C) -346°F ~ 2192°F ±(2%+4°F)	±(1%+1°C) ±(1%+2°F)
	Type T	-200°C ~ 400°C ±(2%+2°C) -346°F ~ 752°F ±(2%+4°F)	±(1%+1°C) ±(1%+2°F)
	Type E	-150°C ~ 1000°C ±(2%+2°C) -238°F ~ 1832°F ±(2%+4°F)	±(1%+1°C) ±(1%+2°F)
	Type R	0°C ~ 1760°C ±(2%+2°C) 32°F ~ 3200°F ±(2%+4°F)	±(1%+1°C) ±(1%+2°F)
	Type S	0°C ~ 1760°C ±(2%+2°C) 32°F ~ 3200°F ±(2%+4°F)	±(1%+1°C) ±(1%+2°F)
	Type N	-200°C ~ 1300°C ±(2%+2°C) -328°F ~ 2372°F ±(2%+4°F)	±(1%+1°C) ±(1%+2°F)
Resolution		≤ 999.9 0.1 > 999.1 1	0.1 1
°C/°F/K Selection		✓	✓
Max Mode		✓	✓
Min Mode		✓	✓
AVG Mode		✓	✓
T2-T1		✓	✓
T4-T3			✓
Hi/Low Alarm			✓
Data Hold		✓	✓
Data Loding		100	5000
Probe Temp Compensation		✓	✓
Auto Calibration		✓	✓
Blue Tooth Interface			✓
Backlight Flashing Alarm		✓	✓
Auto Power Off		✓	✓
Display Backlight		✓	✓
Display Mode			Color LCD
Max Display		9999	9999
Power By		1250mAH Lithium Battery	

* All information provided are subject to change without prior notice.



Your Distributor :

Futronix Co.

HONG KONG

www.futronix-hk.com

info@futronix-hk.com